

# DS201 B16 A10



Products Low Voltage Products and Systems Modular DIN Rail Products Residual Current Devices RCDs  
Residual Current Circuit Breakers with Overcurrent Protection RCBO

## General Information

<b>Extended Product Type:</b>	DS201 B16 A10
<b>Product ID:</b>	2CSR255140R0165
<b>EAN:</b>	8012542995906
<b>Catalog Description:</b>	DS201 B16 A10 - RCBO
<b>Long Description:</b>	The DS201 series RCBO is a 1P+N in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

## Additional Information

<b>Country of Origin:</b>	Italy (IT)
<b>Customs Tariff Number:</b>	85363030
<b>Data Sheet, Technical Information:</b>	2CSC400002D0209
<b>Declaration of Conformity - CE:</b>	9AKK106713A5588
<b>EAN:</b>	8012542995906
<b>EPLAN Catalog Tree:</b>	Electrical engineering / Protection devices / Ground fault current circuit breaker
<b>ETIM 4:</b>	EC000905 - Earth leakage circuit breaker
<b>ETIM 5:</b>	EC000905 - Earth leakage circuit breaker
<b>ETIM 6:</b>	EC000905 - Earth leakage circuit breaker
<b>Environmental Information:</b>	refer to RoHS information
<b>Instructions and Manuals:</b>	9AKK106354A0766
<b>Invoice Description:</b>	DS201 B16 A10 - RCBO
<b>Minimum Order Quantity:</b>	1 piece
<b>Number of Poles:</b>	2
<b>Number of Protected Poles:</b>	1
<b>Object Classification Code:</b>	Q
<b>Operating Characteristic:</b>	Instantaneous
<b>Options Provided:</b>	-
<b>Package Level 1 EAN:</b>	8012542995913
<b>Package Level 1 Gross Weight:</b>	1.446 kg
<b>Package Level 1 Height:</b>	0.088 m
<b>Package Level 1 Length:</b>	0.108 m
<b>Package Level 1 Units:</b>	5 piece
<b>Package Level 1 Width:</b>	0.253 m
<b>Position of Neutral Terminals:</b>	Right
<b>Power Loss:</b>	3.4 W
<b>Product Main Type:</b>	DS201
<b>Product Name:</b>	Residual Current Circuit Breaker with Overcurrent Protection
<b>Product Net Depth:</b>	0.069 m
<b>Product Net Height:</b>	0.085 m
<b>Product Net Weight:</b>	0.239 kg
<b>Product Net Width:</b>	0.035 m
<b>Rated Current (I<sub>n</sub>):</b>	16 A
<b>Rated Operational Voltage:</b>	230-240 V AC
<b>Rated Residual Current:</b>	10 mA
<b>Rated Short-Circuit Capacity (I<sub>cn</sub>):</b>	(230 / 400 V AC) 6 kA
<b>RoHS Date:</b>	20140127
<b>RoHS Information:</b>	2CSC422002K2701
<b>RoHS Status:</b>	Following EU Directive 2011/65/EC
<b>Selling Unit of Measure:</b>	piece
<b>Standards:</b>	IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1
<b>Tripping Characteristic:</b>	B
<b>Type of Residual Current:</b>	A type
<b>Accessories Available:</b>	Yes

